

# 技术资料书

## 玻璃布胶带 产品编号：BT200 (阻燃性)



**说明：** BT200 玻璃布胶带是在 5mm 厚的玻璃纤维上涂覆一层高温硅胶粘合剂而成。用于马达和变压器制造行业，耐高温、坚韧耐磨、阻燃和拉伸强度良好等特点。本产品符合 UL510 阻燃要求。

**应用：** 优秀的机械和电气性能、无腐蚀性，取得 UL 认证，属 N 级绝缘材料。

技术数据：	性能	单位	规格
	基材	-	玻璃布
	颜色	-	白色
	基材厚度	mil/mm	5 / 0.125
	总厚度	mil/mm	7.6 / 0.19
	粘合剂	-	硅胶
	拉伸强度	kg/25mm	60
	伸长率	%	9
	黏着力	kg/25mm	0.65
	击穿电压	kV	3.5
	耐热等级	°C	200

**测试方法：** 根据 ASTM 标准测试

**保存期限：** 6 个月（温度：23°C、湿度：65%）

**包装标准：** 每卷长 33M，宽 980mm，卷心直径 3 英寸

### **Important Notice to Purchase**

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考，如与英文版有歧异之处，一切内容以英文版为准。

