

技术资料书

无纺布挡墙胶带 产品编号：BT860T



说明： BT860T是BT860的增厚版，在聚酯薄膜基材上贴合无纺布，再在无纺布上涂覆一层性能优良的丙烯酸胶粘剂而成。取得UL认证，耐温等级130℃。 PLC=0 CTI 等级 I. 挡墙胶带也叫做无纺布胶带，是在聚酯薄膜基材上贴合无纺布，再在无纺布上单面涂覆一层性能优良的丙烯酸胶粘剂而组成的。它一般有一层、两层、三层的厚度可以供客户进行选择。

特点/优点： 良好的黏着力和耐溶剂性，使用方便，适用于人工作业或机器操作上。

应用： 主要应用于变压器的挡墙及层间绝缘

技术数据：	性能	单位	规格
	总厚度	mm(mil)	0.43 ± 0.03(17.2)
	拉伸强度	kg/25mm(lb/in)	13(28)
	伸长率	%	70
	黏着力	kg/25mm(oz/in)	1.0(35)
	击穿电压	kV	6
	耐热等级	°C	130

测试方法： 根据 ASTM 标准测试

保存期限： 6 个月（温度：23℃、湿度：65%）

包装标准： 每卷长 30M，宽 970mm，卷心直径 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考，如与英文版有歧异之处，一切内容以英文版为准。

