

# TECHNICAL DATA

## Reverse Wound Double Sided Transfer Tape

**Product Code: BT8145**



### Product Code #BT8145 Double Sided Transfer Tape

BT8145 is a clear solvent acrylic reinforced with fibreglass on a brown siliconised paper release liner.

Supplied on a 25mm plastic core to fit a hand held dispenser.

The tape is suitable for external applications due to its humidity and UV resistance.

#### Technical Details :

Adhesive thickness 0.04mm  
Release liner weight 80gsm  
Release liner thickness 77 µm  
Adhesion to steel  
Faced side 3.5 N/cm  
Unfaced side 3.5 N/cm  
RoHS compliant Yes  
Service Temperature -10°C to +100°C  
Application Temperature +15°C to +30°C  
Max Service Temp (short term) -20°C to +130°C  
Storage Temperature +12°C to +25°C

Test Method : In accordance with ASTM method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 50M roll, 3" core, width 1000mm

#### **Important Notice to Purchase**

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

