TECHNICAL DATA

Polyester/Non-Woven Composite Electrical Tape

Product Code: BT818 (Thickness:0.45mm)



712

BT818 Polyester non-woven composite tape is electrical tape is a reinforced, polyester film Description: appearing tape with a pressure sensitive acrylic adhesive. BT818 Tape is especially suited to building coil

barriers. - The thickness and CTI rating facilitates efficiency and effectiveness in this application.

Reduces number of wraps.

The non-woven tapes are available in different variations such as:

Features : Polyester non-woven fabric

Polyacrylate swelling powder

Polyester film

Non-conductive or semi-conductive

Technical Details : PROPERTIES BACKING UNITS SPECIFICATION POLYESTER FILM

TOTAL THICKNESS - 0.45 MM
ADHSION TAPE 15
TENSILE STRENGTH mil / mm 40
ELONGATION mil / mm 1.5

ADHESION TO STEEL - 3.5
DIELECTRIC BREAKDOWN kg/25mm 155
TEMPERATURE RATED

kg/25mm kV °C

Test Method : In accordance with <u>ASTM</u> method

Shelf Life: 6 months when storage at 73°F and 65% relative humidity

Availability: Standard 30M roll, 3" core, width 980mm



All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

