

TECHNICAL DATA

Polyester/Non-Woven Composite

Electrical Tape

Product Code: BT850



Description : BT850 Polyester non-woven composite tape is electrical tape is a reinforced, polyester film tape with a pressure sensitive acrylic adhesive. BT850 Tape is especially suited to building coil barriers. - The thickness and CTI rating facilitates efficiency and effectiveness in this application. Reduces number of wraps.

The non-woven tapes are available in different variations such as:

Features : Polyester non-woven fabric
Polyacrylate swelling powder
Polyester film
Non-conductive or semi-conductive

Technical Details :	<u>PROPERTIES</u>	<u>UNITS</u>	<u>SPECIFICATION</u>
	BACKING	-	POLYESTER FILM
	TOTAL THICKNESS	-	0.13 MM
	ADHSION TAPE	-	15.91
	TENSILE STRENGTH	mil / mm	50
	ELONGATION	mil / mm	1.5
	ADHESION TO STEEL	-	5
	DIELECTRIC BREAKDOWN	kg/25mm	130
	TEMPERATURE RATED	%	
		kg/25mm	
		kV	
		°C	

Test Method : In accordance with ASTM method

Shelf Life : 6 months when storage at 73°F and 65% relative humidity

Availability : Standard 30M roll, 3" core, width 980mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

