

TECHNICAL DATA

CREPE PAPER MASKING RUBBER TAPE

Product Code: BT608



Description : BT608 is a 0.15mm crepe paper tape coated with an aggressive rubber/resin solvent-based adhesive system, recommended for all general purpose 100°C masking applications

Temperature resistance: +120°C up to 60 minutes
Resistant to emulsion and solvent paints.

Features/benefits : Resistant to chemicals, lacquers and solvents.

Suitable for all general purpose 100°C masking applications.
Premium industrial general-purpose masking tape.

Application : Premium automotive masking tape with oven baking resistance.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS	mm	0.15
	TENSILE STRENGTH	kg/25mm	9
	ELONGATION	%	10-20
	ADHESION TO STEEL	kg/25mm	0.6
	DIELECTRIC BREAKDOWN	kV	-
	TEMPERATURE CLASS	°C	100

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 30M roll, 3" core, width 980mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

