

TECHNICAL DATA

POYESTER FILM ELECTRICALTAPE

Product Code: BT012



Description : BT012 is a 0.12mm, electrical insulating tape. It is a flatback Nomex(R) backing with a acrylic adhesive that is flame-retardant and solvent resistant. Unique among insulating tapes: high thermal rating and flame retardancy, along with thinness. An outstanding tape for holding and insulating functions.

Features/benefits : Widely used to hold non-adhesive ground, barrier, and layer insulation in place; to anchor winding starts and ends; to hold edge turns in place; to repair insulation on Nomex-wrapped conductors at splices and terminations; and, as coil end insulation on small stick wound coils.

Application : In small motors, BT012 is valued for insulating connections, bundling end turns, and in multiple layers as ground insulation for small field coils. Also recommended for use in components for home entertainment and telecommunications where flame retardancy is essential.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS	mm	0.12
	TENSILE STRENGTH	kg/25mm	12
	ELONGATION	%	5
	ADHESION TO STEEL	kg/25mm	0.6
	DIELECTRIC BREAKDOWN	kV	155
	TEMPERATURE CLASS	°C	

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 30M roll, 3" core, width 980mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

