TECHNICAL DATA

NOMEX ADHESIVE TAPE

Product Code: BT03S



81

Description :	BT03S is a 0.135mm, electrical insulating tape. It is a flatback Nomex(R) backing with a silicon thermoset adhesive that is flame-retardant and solvent resistant. Unique among insulating tapes: high thermal rating and flame retardancy, along with thinness. An outstanding tape for holding and insulating functions.		
Features/benefits :	Widely used to hold non-adhesive ground, barrier, and layer insulation in place; to anchor winding starts and ends; to hold edge turns in place; to repair insulation on Nomex-wrapped conductors at splices and terminations; and, as coil end insulation on small stick wound coils.		
Application :	In small motors, BT03S is valued for insulating connections, bundling end turns, and in multiple layers as ground insulation for small field coils. Also recommended for use in components for home entertainment and telecommunications where flame retardancy is essential.		
Technical Details :	PROPERTIES TOTAL THICKNESS TENSILE STRENGTH ELONGATION ADHESION TO STEEL DIELECTRIC BREAKDOWN TEMPERATURE CLASS	<u>UNIT</u> mm kg/25mm % kg/25mm kV °C	<u>SPECIFICATION</u> 0.135 12 5 1.0 3 200
Test Method :	In accordance with ASTM D-1000 method		
Shelf Life :	6 months when storage at 23°C and 65% relative humidity		
Availability :	Standard 30M roll, 3" core, width 980mm		

Important Notice to Purchase. All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all waranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer's only obligation shall be to replace such quantity of the product of the use of or "he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.