

TECHNICAL DATA

POYESTER FILM ELECTRICALTAPE

Product Code: BT133



Description : BT133 is 0.055mm polyester film tape made of a 1 mil polyester film coated with an acrylic-based adhesive system, with 0.05 mm total thickness, and recommended for a variety of coil winding, protection, and insulation applications (130°C thermal class B).

Features/benefits : Outstanding dielectric strength.
Acrylic adhesive system designed for its resistance to solvents, freon and transformer oils.
Good peel strength to paints and varnishes

Application : Fixing and securing non-adhesive insulating materials between layers.
Fixing output wires, copper sheets or wire harnesses.
Outer protective insulating wraps for bobbins, transformers, etc.
Soldering protection and varied insulation uses for motors.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS	mm	0.055
	TENSILE STRENGTH	kg/25mm	10
	ELONGATION	%	80
	ADHESION TO STEEL	kg/25mm	0.8
	DIELECTRIC BREAKDOWN	kV	5
	TEMPERATURE CLASS	°C	130

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 30M roll, 3" core, width 980mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

