

TECHNICAL DATA

POLYESTER FILM TAPE Product Code: BT802H



Description : Deaneft manufactures secure and reliable tapes with good insulating properties so that electrical products remain safe. Our polyester tapes are high in strength and difficult to tear or break, offering high resistance to chemicals.

Application : BT802H is a polyester film coated with a pressure sensitive Acrylic adhesive, high dielectric strength, excellent adhesive properties, outstanding heat and Solvent resistant, high tensile and dielectric strength. . it can be used for electrical insulation of coils, electrolytic capacitors, and small transformers, coil and inter-layer insulation, and phase separation of small 3-phase motors.

For the insulation and holding applications in transformers, capacitors, electric motors, relays stabilizers, and various kinds of electronic components. It is used as insulation material for class B.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	FILM THICKNESS	mm	0.038±0.005
	TOTAL THICKNESS	mm	9.5(20.6)(37.24)
	TENSILE STRENGTH	kg/25mm(lb/in)	
	ELONGATION	(N/10mm)	100
	ADHESION TO STEEL	%	
	DIELECTRIC BREAKDOWN	kg/25mm(oz/in)(N/10mm)	0.6(20.8)(2.35)
	TEMPERATURE CLASS		0.8(27.7)(3.13)
		kV	4
	RD = red	°C	130
	GR = green		

* Color : YE = yellow BL = blue

Test Method : In accordance with ASTM method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity Standard

Availability : 50M roll, 3" core, width 960mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

