TECHNICAL DATA

FILAMENT TAPE Product Code: BTG880



71

- BTG880 is manufactured from high performance glass fiber reinforced, polyester film Description with thermosetting rubber pressure sensitive adhesive. Superior tensile strength and adhesion coupled with excellent dielectric value makes this tape ideal for providing a reinforcing functionality in electromechanical equipment.
 - Designed for heavy banding and holding applications, especially those found in large scale coil winding processes such as transformers, motors and generators

Especially suited for heavy duty air and oil filled transformer applications, reinforcements, holding/separating and ground insulation.

: Features/Benefits : Superior tensile strength; Excellent dielectric values

Technical Details :	PROPERTIES POLYESER FILM GLASS FILAMENT TOTAL THICKNESS TENSILE STRENGTH ELONGATION AT BREAK ADHESION TO STEEL BREAKDOWN VOLYAGE HOLDING POWER HEAT RESISTANCE	mm	UNIT mm kg/25mm % kg/25mm kV mm o _C	SPECIFICATION 0.035mm 0.10mm 0.15 <u>+</u> 0.02 100 5 1.6 5 3 130
Availability :	Standard 50M roll, 3" core, width	950mr	n	

6 months when storage at 23°C and 65% relative humidity



All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warrantices, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.