

TECHNICAL DATA

HOT AIR LEVELLING MASKING TAPE

Product Code: BTC5S



Description : BTC5S Hot Air levelling (HAL) masking tape consisting of a polyester film laminated to a masking paper and carrying a silicone adhesive, used for masking in scratch-resistance and impact-resistance, multiple coating for heavy-duty electrostatic power coatings and for multiple connectors of circuit boards in dip soldering or wave soldering, no residual adhesive left. Designed to resist high-pressure air blast associated with HAL process.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	COLOR	-	Red
	TOTAL THICKNESS TENSILE	mm	0.27 ± 0.02 20
	STRENGTH ELONGATION AT	kg/25mm	10
	BREAK	%	250°C x 5 sec.
	WITHSTANDS BRIEF EXPOSURE	°C	

Availability : Standard 33M roll 3" core, width 980mm

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.