

TECHNICAL DATA

POLYESTER TAPE Product Code: BTPET



Description : BTPET is polyester film coated with silicone adhesive. Excellent solvent resistant.; heat resistant and quick grab property, tough and conformable over irregular surfaces, outstanding adhesion over the silicone tube and wire.

Application : Ideal for insulating, banding, anchoring, holding in motors and transformers. Resists the high temperature of molten solder while leaving minimal residue when removed following the process. Reduces clean-up time without danger of breakage or bath contamination.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS mm	-	0.07 ± 0.005
	TENSILE STRENGTH		12
	ELONGATION ADHESION TO STEEL	kg/25mm	60
		%	0.63
		kg/25mm	210 °C
	EXTENDED HEAT-RESISTANCE :30 MINS		Green
	COLOR		

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity Standard

Availability : 33M & 50Meter roll, 3" core, width 640mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.