

技術資料書

玻璃布膠帶 產品編號:BT200 (阻燃性)



說明： BT200 玻璃布膠帶是在 5mm 厚的玻璃纖維上塗覆一層高溫矽膠粘合劑而成。用於馬達和變壓器製造行業，耐高溫、堅韌耐磨、阻燃和拉伸強度良好等特點。本產品符合 UL510 阻燃要求。

應用： 優秀的機械和電氣性能、無腐蝕性，取得 UL 認證，屬 N 級絕緣材料。

技術資料：	性能	單位	規格
	基材	-	玻璃布
	顏色	-	白色
	基材厚度	mil/mm	5/0.125
	總厚度	mil/mm	7.6/0.19
	粘合劑	-	矽膠
	拉伸強度	kg/25mm	60
	伸長率	%	9
	黏著力	kg/25mm	0.65
	擊穿電壓	kV	3.5
	耐熱等級	°C	200

測試方法： 根據 ASTM 標準測試

保存期限： 6 個月（溫度：23°C、濕度：65%）

包裝標準： 每卷長 33M，寬 980mm，卷心直徑 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準

