

技術資料書

KAPTON[®]聚酰亞胺膠帶

產品編號:BT7178

(阻燃性)



UL

說明： BT7178 KAPTON[®]聚酰亞胺膠帶是在 0.025mm 厚的 KAPTON 聚酰亞胺薄膜覆塗一層壓敏丙烯酸酯膠粘劑而成；材質堅韌，防刺穿。本產品符合 UL510 阻燃的要求。

用途： 耐溫等級 155°C，適用各種電氣產品。

技術資料：	性能	單位	規格
	顏色	-	琥珀色(茶色)
	總厚度	mm (mil)	0.063 ± 0.006 (2.5)
	基材厚度	mm (mil)	0.025 (1)
	拉伸強度	kg/25mm (lb/in)	13.6 (29)
	伸長率	%	50
	黏著力	kg/25mm (oz/in)	0.7 (24)
	擊穿電壓	kV	6.0
	溫度等級	C	155

包裝標準： 每卷長 33M、寬 630mm, 卷心直徑 3 英寸

保存期限： 六個月 (溫度：23°C 濕度：65%)

*KAPTON 是美國杜邦公司的註冊商標

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準

